

CHROMA AUSTRALIA PTY LTD ACN 001 594 609 17 MUNDOWI RD MT KURING-GAI NSW 2080, Australia TEL: (02) 9457 9922 FAX: (02) 9457 8082 EMERGENCY TEL: AS ABOVE, or POISONS INFORMATION CENTRE		PAGE 1 of 2 DATE of ISSUE: 1 SEPTEMBER 2006												
Material Safety Data Sheet Not Classified as Hazardous According to the Criteria of Worksafe Australia														
IDENTIFICATION														
<table style="width: 100%; border: none;"> <tr> <td style="width: 60%;">Product name: CHROMACRYL STUDENT ACRYLIC PAINT</td> <td style="width: 40%;">U.N. No: N/A</td> </tr> <tr> <td>Other names: ----</td> <td>Hazchem: N/A</td> </tr> <tr> <td></td> <td>Dangerous Goods Class & Sub Risk: N/A</td> </tr> <tr> <td>Manufacturer's Product Code: VARIOUS</td> <td>Poisons Schedule: N/A</td> </tr> <tr> <td>Use: STUDENT GRADE ACRYLIC PAINT</td> <td></td> </tr> </table>			Product name: CHROMACRYL STUDENT ACRYLIC PAINT	U.N. No: N/A	Other names: ----	Hazchem: N/A		Dangerous Goods Class & Sub Risk: N/A	Manufacturer's Product Code: VARIOUS	Poisons Schedule: N/A	Use: STUDENT GRADE ACRYLIC PAINT			
Product name: CHROMACRYL STUDENT ACRYLIC PAINT	U.N. No: N/A													
Other names: ----	Hazchem: N/A													
	Dangerous Goods Class & Sub Risk: N/A													
Manufacturer's Product Code: VARIOUS	Poisons Schedule: N/A													
Use: STUDENT GRADE ACRYLIC PAINT														
Physical Description/Properties <table style="width: 100%; border: none;"> <tr> <td style="width: 60%;">Appearance: THICK PASTE, VARIOUS COLOURS</td> <td style="width: 40%;">Flash Point (°C): N/A</td> </tr> <tr> <td>Boiling Point/Melting Point (°C) N/A</td> <td>Flammability limits (%): N/A</td> </tr> <tr> <td>Vapour Pressure (pascals or mm of Hg at 25°C) N/A</td> <td>Solubility in Water (g/L): soluble</td> </tr> <tr> <td>Specific Gravity Approx 1g/ml</td> <td></td> </tr> <tr> <td>Other properties</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">SLIGHT AMMONIA SMELL</td> </tr> </table>			Appearance: THICK PASTE, VARIOUS COLOURS	Flash Point (°C): N/A	Boiling Point/Melting Point (°C) N/A	Flammability limits (%): N/A	Vapour Pressure (pascals or mm of Hg at 25°C) N/A	Solubility in Water (g/L): soluble	Specific Gravity Approx 1g/ml		Other properties		SLIGHT AMMONIA SMELL	
Appearance: THICK PASTE, VARIOUS COLOURS	Flash Point (°C): N/A													
Boiling Point/Melting Point (°C) N/A	Flammability limits (%): N/A													
Vapour Pressure (pascals or mm of Hg at 25°C) N/A	Solubility in Water (g/L): soluble													
Specific Gravity Approx 1g/ml														
Other properties														
SLIGHT AMMONIA SMELL														
Ingredients														
Chemical entity	CAS No.	Proportion												
PIGMENT,varied	----	COMMERCIAL IN CONFIDENCE												
ACRYLIC EMULSION	NON HAZ	COMMERCIAL IN CONFIDENCE												
THICKENERS	NON HAZ	<10%												
AMMONIA	7664-41-7	2%												
PRESERVATIVES	149-30-4 / 2634-33-5	0.15%												
WATER	7732-18-5	<40%												
HEALTH HAZARD INFORMATION														
HEALTH EFFECTS:														
Acute: Swallowed	NONE ALLOCATED													
Eye	DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION													
Skin	PROLONGED OR REPEATED CONTACT MAY CAUSE SLIGHT IRRITATION													
Inhaled	INHALATION OF VAPOUR MAY CAUSE IRRITATION													
Chronic	NONE ALLOCATED													
FIRST AID:														
Swallowed	GIVE TWO GLASSES OF WATER TO DRINK													
Eye	FLUSH EYES WITH A LARGE AMOUNT OF WATER													
Skin	WASH AFFECTED AREAS THOROUGHLY													
Inhaled	MOVE SUBJECT TO FRESH AIR													
ADVICE TO DOCTOR TREAT SYMPTOMATICALLY.														

03218310
 03218241
 03218245
 03218284
 03218242
 03218243
 03218245
 03218244
 03218311
 03218251
 03218240
 03218246
 03218309
 03218273
 03218262
 03218435
 03218413
 03218402
 03218436
 03218376
 03218365
 03218424
 03218398
 03218387

PRECAUTIONS FOR USE**EXPOSURE STANDARDS**

NONE

ENGINEERING CONTROLS

USE IN WELL VENTILATED AREAS

PERSONAL PROTECTION

NONE REQUIRED IF USED IN A WELL VENTILATED AREA

FLAMMABILITY

N/A

SAFE HANDLING INFORMATION**STORAGE & TRANSPORT**

KEEP FROM FREEZING. RECOMMENDED STORAGE CONDITIONS ARE BETWEEN 1°C AND 50°C.

SPILLS & DISPOSAL

FOR LARGER QUANTITIES, CONTAIN ANY SPILLS WITH INERT MATERIALS, (SAND, SAWDUST ETC) AND TRANSFER TO CONTAINERS FOR DISPOSAL. KEEP SPILL OUT OF OPEN BODIES OF WATER. OBSERVE EPA REGULATIONS. SOAK UP SMALLER SPILLS WITH A RAG AND DISPOSE OF CAREFULLY.

FIRE/EXPLOSION HAZARD

NOT APPLICABLE

OTHER INFORMATION**CONTACT POINT**

MT KURING-GAI AUSTRALIA

DATE OF ISSUE: 1 SEPTEMBER 2006