

FLEET (LINE MARKERS) LTD Fleet House Spring Lane Malvern Worcestershire **WR14 1AT** U.K. Tel: +44 (0) 1684 573 535 Fax: +44 (0) 1684 892 784

PRODUCT HEALTH AND SAFETY

COMPANY PRODUCT AND COMPANY IDENTIFICATION 1.

PRODUCT NAME: PRODUCT PURPOSE: COMPANY IDENTIFICATION:

SUPERWHITE DRY LINE MARKING (OUTDOOR) FLEET (LINE MARKERS) LTD. Fleet House, Spring Lane, Spring Lane Industrial Estate, Malvern, Worcs. WR14 1AT +44(0) 1684 573535 +44(0) 1684 892784 sales@fleetlinemarkers.com +44(0) 1684 573535

Dust Inhalation

TEL: FAX: E-MAIL: **EMERGENCY TELEPHONE**

2. HAZARD IDENTIFICATION

PRIMARY ROUTES OF EXPOSURE:

INHALATION:

EYE CONTACT: SKIN CONTACT:

3. COMPOSITION

Calcium carbonate powder.

FIRST AID MEASURES 4.

INHALATION; EYE CONTACT:

SKIN CONTACT: INGESTION:

Eve Contact Skin Contact Prolonged exposure to limestone dust may cause respiratory problems. Direct contact with this material may cause irritation. Prolonged or repeated contact may cause dryness of the skin and irritation.

Remove to fresh air. Flush eyes with large amounts of water. Seek medical advice if irritation persists. Wash with soap and water. Wash out mouth with water. Seek medical attention if person feels unwell.

FIRE FIGHTING MEASURES 5.

Not flammable.

ACCIDENTAL RELEASE MEASURES 6.

Avoid creating dust. Collect by vacuum cleaning, or hose away with plenty of water.

7. HANDLING AND STORAGE

HANDLING: STORAGE:	Use appropriate controls to avoid creating dust. Store in a dry covered area. Do not store near acids.
8. EXPOSURE CONTROLS AND PERSONAL PROTECTION	
EXPOSURE CONTROLS:	Ensure occupational exposure limits are maintained. (Long term exposure limit for total inhalable dust 10mg/m ³ , 8h TWA and respirable dust 4mg/m ³ , 8h TWA - UK EH40/99)
PERSONAL PROTECTION:	,
Respiratory:	Wear appropriate safety dust mask if conditions are dusty.
Hand:	Gloves, if risk of skin contact.

1of 3





PRODUCT HEALTH AND SAFETY

Eye: Skin: Wear safety glasses. Provide eyewash. Standard industrial overalls.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Odour: pH: Boiling point: Specific Gravity: Water solubility: Off-white powder. None 8.5 - 9.5 N/A 2.6 - 2.8 Virtually insoluble

10. STABILITY AND REACTIVITY

Superwhite is stable under normal conditions of use - also see Handling and Storage. Materials to avoid: Acids. Reacts with acids forming carbon dioxide.

11. TOXICOLOGICAL INFORMATION

This product is regarded as non-toxic.

12. ECOLOGICAL INFORMATION

Not biodegradable, inert.

13. DISPOSAL INFORMATION

Superwhite is not classified as hazardous waste. This product can be disposed of as non-toxic waste in approved sites in accordance with local regulations.

14. TRANSPORT INFORMATION

Superwhite is not classified as hazardous for transportation.

15. REGULATORY INFORMATION

Classification and Labelling: Complies with EEC Directives, U.K. EH40 and COSHH guidelines.

16. OTHER INFORMATION

Fleet (Line Markers) Ltd. classifies this product as non-hazardous or toxic under normal conditions of use. The information provided in this Safety data Sheet is based on the present state of our knowledge. This data is intended to enable safety assessments to be carried out and should not be construed as a guarantee of specific properties.

Date of issue: January 20th 2009

Revision Reference: 004

